







## AGRICULTURAL /INDUSTRY





**S**T TRADING

HEXAGON HEAD BOLT HALF THREAD



2



HEXAGON HEAD FLANGE BOLT



SCREW PLUG



**U BOLTS** 




**FLAT WASHER** 



**HEXAGON NUT** 

/ 4







PREVAILING TORQUE TYPE HEXAGON NUT, ALL METAL



**CASTLE NUTS** 

13



SPECIAL ITEMS



SPECIAL ITEMS





SPECIAL ITEMS







### SOLAR

We manufacture a complete range of unique headed and threaded fasteners in a wide variety of sizes and lengths for a multitude of SOLAR ENERGY applications. Our commitment to the SOLAR Industry is ongoing through strategic partnerships with world-class manufacturers. We continue to provide our customers with superior technical support and other application engineering services and ensure the availability of ideal fastener concepts.

STD has a large range of articles with surface coating e.g geomet321,500a/b,deltaprotech,zintech,zincnikel. Also tuflok90-180, precote 3m, tuflok360. and omnimask.

View our STD Products for fastening solutions in SOLAR industry



#### HEXAGON HEAD FLANGE BOLT INOX



HEXAGON FLANGE NUT INOX



HEXAGON NUTS INOX



FLAT WASHERS



SPRINC LOCK WASHERS INOX



SPRING LOCK WASHER

COATING TYPES' CHARACTERISTICS TABLE									
PLATING DESCRIPTION	COATING THICKNESS	COATING WEIGHT	SALT SPRAY RESISTANCE		FRICTION				
			WHITE CORROSION	RED CORROSION	COEFFICIENT	DESCRIPTION OF			
GEOMET® 321A	6-8 µm	≥24 gr/m <sup>2</sup>	>240 h	≥720 h	0,06-0,20	%100 free from Chrome and heavy metal.			
GEOMET® 321B	8-10 µm	≥36 gr/m <sup>2</sup>	×240 II	≥1000 h	Silver gray colored coating				
GEOMET® 500A	6-8 µm	≥24 gr/m²	>240 h	≥720 h	0,12-0,18	%100 free from Chrome and heavy metal.			
GEOMET® 500B	8-10 µm	≥36 gr/m <sup>2</sup>	≥1000 h		0,12-0,10	Low friction coefficient, gray coating			
GEO.321A/GEO.500A+PLUS® L	-	≥26 gr/m <sup>2</sup>		≥720 h	0,08-0,14	Over Geomet colorless, protective coating			
GE0.321B/GE0.500B+PLUS® L	-	≥38 gr/m <sup>2</sup>		≥1000 h		over deomet coloness, protective couting			
GE0.321A/GE0.500A+PLUS® VL	-	≥26 gr/m <sup>2</sup>	-	≥720 h		Over Geomet colorless, protective coating			
GEO.321B/GEO.500B+PLUS® VL	-	≥38 gr/m²		≥1000 h	0,09-0,14	over deamer coloness, protective coulding			
GEO.321A/GEO.500A+PLUS® VLh	-	≥29 gr/m <sup>2</sup>		≥720 h	0,05 0,14	Over Geomet colorless, protective coating			
GEO.321B/GEO.500B+PLUS® VLh	-	≥41 gr/m <sup>2</sup>		≥1000 h		over deomet coloness, protective couting			
GEO.321A/GEO.500A+PLUS® M	-	≥26 gr/m <sup>2</sup>	_	≥720 h	0,12-0,18	Over Geomet colorless, protective coating			
GEO.321B/GEO.500B+PLUS® M	-	≥38 gr/m <sup>2</sup>		≥1000 h		e tel econici esterios, protective couting			
GEO.321A/GEO.500A+PLUS® ML	-	≥26 gr/m²	_	≥720 h	0.10-0.16	Over Geomet colorless, protective coating			
GEO.321B/GEO.500B+PLUS® ML	-	≥38 gr/m <sup>2</sup>		≥1000 h	0,10 0,10				

#### COATING TYPES' CHARACTERISTICS TABLE

PLATING DESCRIPTION	COATING THICKNESS	COATING	SALT SPRAY	RESISTANCE	FRICTION	DESCRIPTION OF		
		WEIGHT	WHITE CORROSION	RED CORROSION	COEFFICIENT			
GEO.321A/GEO.500A+PLUS® XL	-	≥26 gr/ <sub>m</sub> 2		≥720 h	0.06-0.09	Over Geomet colorless, protective coating		
GEO.321B/GEO.500B+PLUS® XL	-	≥38 gr/m <sup>2</sup>	- ≥1000 h		0,00-0,09	over Geomer coloness, protective coating		
GE0.321A/GE0.500A+PLUS® 10	-	≥26 gr/m²	_	≥720 h	> 0,18	Over Geomet colorless, protective coating		
GE0.321B/GE0.500B+PLUSv 10	-	≥38 gr/m²		≥1000 h	2 0,10	(Physical strength increases.not lubricated)		
GEO.321A/GEO.500A+PLUS® ML BLACK	-	≥32 gr/m <sup>2</sup>		≥1000 h	0,10-0,16	black, protective top coat		
GEO.321B/GEO.500B+PLUS® ML BLACK	-	≥44 gr/m <sup>2</sup>	-			black, protective top coat		
GEO.500A+PLUS® Black	_	≥32 gr/m²						
500 M (GEOBLACK® 500M)		252 gi/11-	≥32 gi/iii²		0,10-0,16	black, protective top coat		
GEO.500B+PLUS® Black	-	≥44 gr/m²						
500 M (GEOBLACK® 500M)								
GEO.321A/GEO. 500A+DACROLUB®10B/G/L	-	≥26 gr/m <sup>2</sup>	≥720 h					
GEO.321B/GEO.			-		0,08-0,14			
500B+DACROLUB®10B/G/L	-	≥38 gr/m²		≥1000 h		Geomet colored coating over		
GEO.321A/GEO.500A+PLUS®	-	≥28 gr/m²		≥720 h		(DACROLUB10B:BLUE, DACROLUB 10G:GREEN) DACROLUB 10L colorless coating		
L+DACROLUB® 10B/10G/10L			_		0,08-0,14			
GEO.321B/GEO.500B+PLUS®	-	≥40 gr/m <sup>2</sup>		≥1000 h				
L+DACROLUB® 10B/10G/10L								

#### COATING TYPES' CHARACTERISTICS TABLE

PLATING	APPEARANCE	SALT SPRAY RESISTANCE		FRICTION	TEMPERING HYDROJEN EMBRILMENT RELIEFING			
DESCRIPTION		WHITE CORROSION	RED CORROSION	COEFFICIENT	8.8	10.9	12.9	
Delta Protekt KL 100	Silver Grey	-	480 h	0,12-0,30	-	-	-	
Delta Protekt KL 100	Silver Grey	-	600 h	0,12-0,30	-	-	-	
Delta Protekt KL 100+ VH301 GZ	Silver Grey	-	720 h	0,09-0,14	-	-	-	
Delta Protekt KL 100 +VH302 GZ	Silver Grey	-	720 h	0,11-0,17	-	-	-	
Delta Protekt KL 100+Delta Seal GZ Black	Black	-	720 h	0,09-0,14	-	-	-	

## /TRAILER PRODUCERS

TRADING





HEXAGON HEAD BOLT FULL THREAD



LARGE SIZE WASHER



HEXAGON HEAD BOLT FINE THREADED UP TO HEAD



BUTTON HEAD SOCKET SCREW



HEXAGON NYLON INSERT NUT

## VALVE MANUFACTURERS

/





HEXAGON NUTS INOX



THREADED ROD INOX



HEXAGON SOCKET HEAD CAP SCREWS INOX



HEXAGON HEAD BOLT FULL THREAD INOX



HEXAGON SOCKE SCREW WITH CUP POINT INOX

## AGRICULTURAL STORAGE FASTENERS

#### **METRIC SILO BOLT**

#### FASTENERS FOR THE GRAIN BIN AND STORAGE BUILDING INDUSTRIES

NORM FASTENERS Grain Bin and Storage Building fasteners receive the new NORMTECH extreme life plating as NORM's standard finish.

- Included in this product range are fasteners made to Property Class 8.8 and 10.9
- Various types of nuts are produced from finished hexagon, heavy semi-finished, flange, (both plain and serrated) nuts.
- NORMTECH has been proven to remain completely rust-free in over 800 hours of salt spray testing. That's up to 20 times more corrosion resistance than electro zinc platings and considerably better than certain post-plating coatings on the market.
- NORMTECH With the help of special layers applied upon zinc coating; NormTech designed to renew itself to last very longer. Because it is a renewable coating type, early corrosion problems caused by small mechanical damage are prevented. This ensures that the connections can be used for a longer period of time without corrosion.
- Sealing Washer: Specially designed by Norm Fastaners, It has a special polypropylene, therewithal unbreakable and resistant to a temperature -20°C / +120°C.
- Standart Zinc: 80-100 hours to red rust in salt spray, but NORMTECH : For the 21st Centry 800 hours to red rust in salt spray.

## **Friend of Silos**



#### **METRIC SILO BOLT**

## 

#### Kitting of sets and assembly kits

- For assembling agricultural storage industries and repair kits for spare parts stores, we have setsand assembly kits toincrease efficiency in the agricultural storage sector STD Kitting & Packaging fulfils every customer-specific requirement.
- With Assembling kits offers a better service to our customers , most importantly we save time for the our customers.



#### Packaging Types

- Round Plastic Pails: Bulk packed, waterproof & resealable
- Cartoons Box: Small than box or bluk packed.



# MINING INDUSTRY







J BOLT



HEXAGON HEAD BOLT HALF THREAD



T BOLT



HEXAGON NUT



HEXAGON HEAD BOLT FULL THREAD

## FURNITURE

# PVC-WINDOWS







CHIPBOARD SCREWS



**HEXAGON NUT** 



PHIL CROSS RECESSE PAN HEAD SCREW



CYLINDER THIN HEAD RIVET NUT



HEXAGON WASHER HEAD SELF DRILLING SCREW



CYLINDER FLAT HEAD RIVET NUT





MODULAR CONNECTION PARTS



TABLE SLIDES

FURNITURE





COLLATED SEL DRILLING DRYWALL SCREWS



CROSS RECESSED COUNTERSUNK HEAD SELF DRILLING SCREW



CHIPBOARD SCREWS



HEXAGON SOCKET HEAD CAP SCREW



MUSHROOM HEAD SQUARE NECK BOLT



**STUD BOLTS** 



**TEE NUTS** 





**HEXAGON NUT** 



FLAT WASHER



WING NUT PLASTIC COATED



T NUT




HEXAGON NYLON INSERT NUT



HEXAGON DOMED CAP NUT

/





**TELESCOPIC SLIDES** 



**CONCEALED SLIDES** 



WALL HANGING BRACKETS



FULLOVERLAY HINGES



HALFOVERLAY HINGES



**INSET HINGES** 















25





PKM 80 ADJUSTIBLE SLIDIN DOOR ROLLER



**INSET HINGES** 



TELESCOPIC SLIDES



HYDROLIC HINGES



FULLOVERLAY HINGES




**GAS SPRING** 



HALFOVERLAY HINGES



**BACKING SCREW** 





HIDDEN SHELF HOLDER



PHIL CROSS RECESSED PAN HEAD SCREW



CHIPBOARD SCREWS



**SHELF PIN** 



**BACKING PINS** 







**CONCRETE SCREW** 



**HI-LOW SCREW** 



CROSS RECESSED COUNTERSUNK HEAD SELF DRILLING SCREW



ALUMINIUM WINDOW HANDLE



ZAMAK HINGES



CROSS RECESSED PAN HEAD SELF DRILLING SCREW



PLISSE WIREMESH







**CONCRETE SCREW** 



**HI-LOW SCREW** 



CROSS RECESSED PAN HEAD SELF DRILLING SCREW



CROSS RECESSED OUNTERSUNK HEAD SELF DRILLING SCREW



ALUMINIUM DOOR HANDLE



ZAMAK HINGES



FIBERGLASS WIREMASH



WEATHER STRIPS









**ST Trading SP. Z O.O.** ul. Św. Mikołaja 1, 62-080 Swadzim KRS: 0000737131, NIP: 9291954400 REGON: 380548120

